

Pressure / Vacuum Switches

Option	Base Thread Size*	SM	MM	LM	CJ	XM	WX	CD	VM	NV	VP
1	1/4 – 18 NPT Male	•	•	•	•	•	•	•	•	•	•
2	1/8 – 27 NPT Male	•	•	•	•	•	•	•	•	•	•
3	3/4 – 16 UNF SAE O-Ring (-5)	•	•		•	•	•	•	•	•	
4	7/16 – 20 37° JIC Flare (-4)			•		•	•				
5	1/4 – 18 NPT Female	•	•			•	•	•			
6	7/16 – 20 SAE O-Ring (-4)	•	•	•		•	•	•		•	•
7	1/4 – 18 NPT Female (Obsolete) See Option 5										
8	1/8 NPT Female	•	•			•	•		•	•	•
9	3/8 – 18 NPT	•	•	•		•	•	•	•		
10	1/4 Female Stainless Steel (Obsolete) See Option 5										
11	9/16 SAE O-Ring (-6)	•	•	•	•	•	•	•	•		•
12	M10 x 1 SAE J2244-3	•	•	•	•	•	•				
13	1/2 – 20 UNF SAE O-Ring (-5)	•	•			•	•		•		•
14	1/2 NPT Male 1/8 NPT Female	•	•							•	
15	7/16 – 20 Female SAE O-Ring (D4)					•	•				
16	7/16 – 20 Female SAE J 514 37 DEG			•		•	•				
17	1/4 BSPP (G1/4)	•	•	•	•	•	•	•	•	•	•
18	7/16 – 20 ADJ					•	•				
19	1/8 BSPT JIS (PT) Taper	•	•	•		•	•				
20	Tri-Clover					•	•				
21	1/4 BSPP Extended (G1/4)	•	•			•	•		•		
22	1/2 – 14 NPT Brass Male (IS Only)										
23	1/4 – 18 NPT SS Female (IS Only)										
24	10/32 INT 3/8 – 24 EXT	•	•								
25	1/4 NPT Plastic (Obsolete) See Option 1										
26	9/16 – 18 Female 37 DEG SAE J 514 (-6)			•		•	•	•			
27	1/2 BSPT – Male (R12)	•	•						•		
28	1/8 BSPP (G1/8)	•	•		•						
29	3/8 – 24 SAE O-Ring (-3)	•	•			•	•				
30	1/4 BSPT (JIS) (R1/4)	•	•					•	•		
31	Flange (NS Only)										
32	M12 – 1.5 Metric	•	•								
33	Extended Flange (NS Only)										
34	7/16 – 20 MS33649 Female* 14 NPTE (Male)					•	•				
35	1/2 – 14 NPT (Male)			•		•	•				
36	9/16 O-Ring Extended Boss (-6)			•		•	•				
37	3/8 – 24 Inverted Flare	•	•	•							
38	9/16 – 12 UNC (SR Only)									•	

*Call Nason at 800.229.4955 if you don't see the media connection that fits your application.

Note: Consult factory for materials and stock.