

Temperature Switches

Option	Base Thread Size*	TD	TM/HT	TT Model Probe Code					
				D 1/2" Probe	E 3/4" Probe	F 1" Probe	G 1-1/4" Probe	H 1-1/2" Probe	J 2" Probe
1	1/2 NPT Male	•	•	•	•	•	•	•	•
2	3/8 NPT Male	•	•	•	•	•		•	•
3	1/4 NPT Male			•	•	•		•	•
4	3/8 NPT (1PC)		•						
5	3/4 – 16 SAE O-Ring (-8)	•	•	•	•	•		•	•
6	M16 x 1.5		•	•		•			•
7	1/2 BSPP	•	•		•				
8	1/2 NPT (1PC)		•						
9	3/8 NPT (Short)		•						
10	M14 x 1.5 (Nickel Plated)				•				
11	M14 x 1.5				•	•			
12	1/2 NPT (Nickel Plated)		•				•		
13	1/4 NPT (316SS)			•		•			
14	1/2 BSPP Extended		•						
15	3/4 – 16 SAE O-Ring (-8) Short		•						
16	3/8 – 19 BSPT/JIS	•	•	•					
17	M18 x 1.5 SAE J2244	•	•	•	•	•			
18	1/4 NPT (Nickel Plated)			•	•				
19	1/2 NPT (316SS-1PC)		•			•			
20	1/2 NPT (Very Short)		•						
21	3/8 NPT (Very Short)		•						
22	M16 x 1.5 (Flare)				•				
23	1/2 BSPT (R1/2)		•						
24	1/2 NPT (316SS)					•			
25	3/8 NPT (Nickel Plated) 1PC		•						

*Call Nason at 800.229.4955 if you don't see the media connection that fits your application.

Note: Consult factory for materials and stock.